



**CEYQUARTZ MBI (PVT) LTD.**



"Dutch house"  
34/1, Castle Street, Colombo 8,  
Sri Lanka  
Phone: +94112667704-5 Fax:  
+94112696515

## PRODUCT INFORMATION

### CML 115-005

PRODUCTION SITE: NAULA ,SRI LANKA ( CERTIFIED ISO 9001:2015 & ISO 14001:2015)

SHORT DESCRIPTION OF THE PRODUCT: NATURAL CRUSHED HIGH PURITY QUARTZ POWDER

SPECIFIC PRODUCT DATA:  
DISTRIBUTION.

|                    |              |           |
|--------------------|--------------|-----------|
| Wet Sieving Method | + 212µm      | 0         |
|                    | + 150 µm     | 0         |
|                    | + 106 µm     | 0.2 Max   |
|                    | + 75 µm      | 2.0 Max   |
|                    | CILAS Method |           |
|                    | D50          | 10.6-14.6 |
|                    | D97          | 115       |
|                    | < 6 µm       | 26.7-36.7 |

|                    |                                |               |
|--------------------|--------------------------------|---------------|
| CHEMICAL ANALYSIS: | SiO <sub>2</sub>               | : 99.8 % Min  |
|                    | Al <sub>2</sub> O <sub>3</sub> | : 500 ppm Max |
|                    | Fe <sub>2</sub> O <sub>3</sub> | : 50 ppm Max  |
|                    | MgO                            | : 10 ppm Max  |
|                    | K <sub>2</sub> O               | : 30 ppm Max  |
|                    | Na <sub>2</sub> O              | : 30 ppm Max  |
|                    | CaO                            | : 30 ppm Max  |

|                          |                  |              |
|--------------------------|------------------|--------------|
| IONIC IMPURITY ANALYSIS: | Cl <sup>-</sup>  | : 10 ppm Max |
|                          | Na <sup>+</sup>  | : 10 ppm Max |
|                          | Fe <sup>2+</sup> | : 11 ppm Max |

|                         |         |
|-------------------------|---------|
| Electrical Conductivity | 10 Max  |
| pH                      | 6.1-7.1 |
| Moisture                | 0.1 Max |
| MFM (45 µm) pcs/50g     | 50 Max  |

|      |        |            |
|------|--------|------------|
| ROHS | Cd     | : < 2 ppm  |
|      | Cr(vi) | : < 2 ppm  |
|      | Hg     | : < 2 ppm  |
|      | Pb     | : < 2 ppm  |
|      | PBBs   | : < 5 ppm  |
|      | PBDEs  | : < 5 ppm  |
|      | BBP    | : < 50 ppm |
|      | DBP    | : < 50 ppm |
|      | DEHP   | : < 50 ppm |
|      | DIBP   | : < 50 ppm |

STANDARD PACKAGING:- BIG BAG on pallet

Edition : 2020.11.11